



# ステンレス六角棒 (JIS G4318)

## SUS 304 (冷間引抜)

対辺 (mm)	長さ (mm)	質量 (kg/本)	寸法公差
8	×	4000	1.76 +0 ~ -0.15
10	×	4000	2.75 +0 ~ -0.15
12	×	4000	3.97 +0 ~ -0.18
13	×	4000	4.64 +0 ~ -0.18
14	×	4000	5.40 +0 ~ -0.18
17	×	4000	7.92 +0 ~ -0.18
19	×	4000	9.92 +0 ~ -0.21
21	×	4000	12.1 +0 ~ -0.21
22	×	4000	13.3 +0 ~ -0.21
23	×	4000	14.5 +0 ~ -0.21
24	×	4000	15.8 +0 ~ -0.21
26	×	4000	18.6 +0 ~ -0.21
27	×	4000	20.0 +0 ~ -0.21
29	×	4000	13.1 +0 ~ -0.21
30	×	4000	24.7 +0 ~ -0.21
32	×	4000	28.1 +0 ~ -0.25
35	×	4000	33.6 +0 ~ -0.25
36	×	4000	35.6 +0 ~ -0.25
38	×	4000	39.7 +0 ~ -0.25
41	×	4000	46.0 +0 ~ -0.25
46	×	4000	58.0 +0 ~ -0.25
50	×	4000	68.8 +0 ~ -0.25
54	×	4000	80.0 +0 ~ -0.30
55	×	4000	83.2 +0 ~ -0.30
60	×	4000	98.8 +0 ~ -0.30

## SUS 304 (熱間引抜)

対辺 (mm)	長さ (mm)	質量 (kg/本)	寸法公差
58	×	3000up	23.1 +0 ~ -0.46
63	×	3000up	27.2 +0 ~ -0.46
65	×	3000up	29.0 +0 ~ -0.46
67	×	3000up	30.8 +0 ~ -0.46
70	×	3000up	33.6 +0 ~ -0.46
75	×	3000up	38.6 +0 ~ -0.46
80	×	3000up	43.9 +0 ~ -0.46
85	×	3000up	49.6 +0 ~ -0.54
90	×	3000up	55.6 +0 ~ -0.54