

溶接管：TP-A (JIS G3459)

SUS 304

外径 (mm)	×	厚さ (mm)	×	長さ (mm)	質量 (kg/m)
6	×	0.5	×	4000	0.069
		1.0	×	〃	0.125
6.35	×	1.0	×	〃	0.133
7	×	1.0	×	〃	0.149
8	×	0.5	×	〃	0.093
		1.0	×	〃	0.174
		1.5	×	〃	0.243
9	×	1.0	×	〃	0.199
9.53	×	1.0	×	〃	0.212
10	×	0.5	×	〃	0.118
		1.0	×	〃	0.224
		1.5	×	〃	0.318
		2.0	×	〃	0.399
10.5	×	1.0	×	〃	0.237
		1.2	×	〃	0.278
		1.5	×	〃	0.335
		2.0	×	〃	0.423
12	×	0.5	×	2000	0.143
		1.0	×	4000	0.274
		1.5	×	〃	0.392
		2.0	×	〃	0.498
12.7	×	1.0	×	〃	0.241
		1.5	×	〃	0.418
		2.0	×	〃	0.533
13	×	1.0	×	〃	0.299
13.8	×	1.2	×	〃	0.378
		1.5	×	〃	0.460
		2.0	×	〃	0.588
		2.2	×	〃	0.636
		3.0	×	〃	0.807
14	×	1.0	×	〃	0.324
15	×	1.0	×	〃	0.349
		1.5	×	〃	0.504
		2.0	×	〃	0.648
16	×	1.0	×	〃	0.374
		1.5	×	〃	0.543

外径 (mm)	×	厚さ (mm)	×	長さ (mm)	質量 (kg/m)
16	×	2.0	×	4000	0.698
17.3	×	1.2	×	〃	0.480
		1.5	×	〃	0.590
		2.0	×	〃	0.762
		2.5	×	〃	0.922
		3.0	×	〃	1.07
18	×	1.0	×	〃	0.423
19	×	1.0	×	〃	0.448
		1.2	×	〃	0.533
		1.5	×	〃	0.655
		2.0	×	〃	0.848
20	×	1.0	×	〃	0.473
		1.5	×	〃	0.691
		2.0	×	〃	0.897
21.7	×	1.2	×	〃	0.613
		1.5	×	〃	0.755
		2.0	×	〃	0.981
		×		6000	0.981
		2.5	×	4000	1.20
		×		5000	1.20
		×		6000	1.20
		3.0	×	4000	1.40
		×		6000	1.40
22	×	1.0	×	4000	0.523
25	×	1.0	×	〃	0.598
		1.5	×	〃	0.878
		2.0	×	〃	1.15
25.4	×	1.2	×	〃	0.723
		1.5	×	〃	0.893
		2.0	×	〃	1.17
		3.0	×	〃	1.67
27.2	×	1.2	×	〃	0.778
		1.5	×	〃	0.960
		2.0	×	〃	1.26
		×		5500	1.26
		×		6000	1.26

溶接管：TP-A (JIS G3459)

SUS 304

外径 (mm)	×	厚さ (mm)	×	長さ (mm)	質量 (kg/m)
27.2	×	2.5	×	4000	1.54
			×	5500	1.54
			×	6000	1.54
		3.0	×	4000	1.81
			×	6000	1.81
30	×	1.5	×	4000	1.06
		2.0	×	〃	1.39
		3.0	×	〃	2.02
32	×	1.2	×	〃	0.920
		1.5	×	〃	1.14
		2.0	×	〃	1.49
		3.0	×	〃	2.17
34	×	1.2	×	〃	0.980
		1.5	×	〃	1.21
		2.0	×	〃	1.59
			×	6000	1.59
		2.5	×	4000	1.96
		3.0	×	〃	2.32
			×	6000	2.32
		3.5	×	4000	2.66
			×	6000	2.66
		4.0	×	4000	2.99
			×	6000	2.99
38	×	1.5	×	4000	1.36
		2.0	×	〃	1.79
		3.0	×	〃	2.63
40	×	2.0	×	〃	1.89
42.7	×	1.2	×	〃	1.24
		1.5	×	〃	1.54
		2.0	×	〃	2.03
			×	6000	2.03
		3.0	×	4000	2.97
			×	6000	2.97
		3.5	×	4000	3.42
			×	6000	3.42
		4.0	×	4000	3.86

外径 (mm)	×	厚さ (mm)	×	長さ (mm)	質量 (kg/m)
42.7	×	4.0	×	6000	3.86
45	×	2.0	×	4000	2.14
48.6	×	1.2	×	〃	1.42
		1.5	×	〃	1.76
		2.0	×	〃	2.32
			×	6000	2.32
		3.0	×	4000	3.41
			×	6000	3.41
		3.5	×	4000	3.93
			×	6000	3.93
		4.0	×	4000	4.44
			×	6000	4.44
		5.1	×	4000	5.53
			×	6000	5.53
50.8	×	1.5	×	4000	1.84
		2.0	×	〃	2.43
		3.0	×	〃	3.57
60.5	×	1.5	×	〃	2.20
		2.0	×	〃	2.91
			×	6000	2.91
		3.0	×	4000	4.30
			×	6000	4.30
		3.5	×	4000	4.97
			×	6000	4.97
		4.0	×	4000	5.63
			×	6000	5.63
		5.0	×	4000	6.90
		5.5	×	〃	7.54
			×	6000	7.54
63.5	×	2.0	×	4000	3.06
76.3	×	1.5	×	〃	2.80
		2.0	×	〃	3.70
			×	6000	3.70
		3.0	×	4000	5.48
			×	6000	5.48
		3.5	×	4000	6.35

溶接管：TP-A (JIS G3459)

SUS 304

外径 (mm)	×	厚さ (mm)	×	長さ (mm)	質量 (kg/m)		
76.3	×	3.5	×	6000	6.35		
				4000	7.20		
			×		6000	7.20	
					4000	8.88	
			×		6000	8.88	
					4000	12.1	
	×		6000	12.1			
			4000	12.1			
89.1	×	2.0	×	4000	4.34		
				6000	4.34		
		3.0	×		4000	6.43	
					6000	6.43	
		4.0	×		4000	8.48	
					6000	8.48	
		5.0	×		4000	10.5	
					6000	11.5	
		5.5	×		4000	11.5	
					6000	15.4	
		7.6	×		4000	15.4	
					6000	15.4	
101.6	×	2.0	×	4000	4.96		
				6000	4.96		
		3.0	×		4000	7.37	
					6000	7.37	
		4.0	×		4000	9.72	
					6000	9.72	
		5.7	×		4000	13.6	
					6000	13.6	
		8.1	×		4000	18.9	
					6000	18.9	
		114.3	×	2.0	×	4000	5.59
						6000	5.59
3.0	×				4000	8.32	
					6000	8.32	
4.0	×				4000	11.0	
					6000	11.0	
5.0	×				4000	13.6	
					6000	16.2	

外径 (mm)	×	厚さ (mm)	×	長さ (mm)	質量 (kg/m)	
114.3	×	6.0	×	6000	16.2	
				4000	22.6	
			×		6000	22.6
					4000	22.6
139.8	×	2.0	×	4000	6.88	
				4000	10.2	
			×		6000	10.2
					4000	11.9
			×		6000	11.9
					4000	13.5
			×		6000	13.5
					4000	16.8
			×		6000	16.8
					4000	21.9
			×		6000	21.9
					4000	30.8
	×		6000	30.8		
			4000	30.8		
165.2	×	2.0	×	4000	8.13	
				4000	12.1	
			×		6000	12.1
					4000	14.1
			×		6000	14.1
					4000	16.1
			×		6000	16.1
					4000	20.0
			×		6000	20.0
					4000	28.0
			×		6000	28.0
					4000	42.3
	×		6000	42.3		
			4000	42.3		
190.7	×	3.0	×	4000	14.0	
				4000	18.6	
		6.0	×	4000	27.6	
216.3	×	3.0	×	4000	15.9	
				6000	15.9	
		4.0	×		4000	21.2
					6000	21.2

溶接管：TP-A (JIS G3459)

SUS 304

外径 (mm)	×	厚さ (mm)	×	長さ (mm)	質量 (kg/m)		
216.3	×	5.0	×	4000	26.3		
				6000	26.3		
	6.0	×	4000	×	6000	31.4	
							6.5
	8.2	×	4000	×	6000	42.5	
							12.7
	267.4	×	3.0	×	4000	19.8	
					6000	19.8	
		3.5	×	4000	×	6000	23.0
		5.0	×	4000	×	6000	32.7
9.3		×	4000	×	6000	59.8	
							15.1
318.5		×	3.0	×	4000	23.6	
					6000	23.6	
		4.0	×	4000	×	6000	31.3
	6.0	×	4000	×	6000	46.8	
							6.5
	10.3	×	4000	×	6000	79.1	
							17.4

外径 (mm)	×	厚さ (mm)	×	長さ (mm)	質量 (kg/m)		
318.5	×	17.4	×	6000	131.0		
				355.6	×	4.0	×
6000	35.0						
5.0	×	4000	×		6000	43.7	
							6.0
6.5	×	6000	×		6000	56.5	
							8.0
11.1	×	4000	×		6000	95.3	
							19.0
406.4	×	4.0	×		4000	40.1	
					6000	40.1	
	5.0	×	4000		×	6000	50.0
	6.5	×	4000	×	6000	59.8	
							8.0
	12.7	×	4000	×	6000	125.0	
							457.2
	6000	45.2					
	5.0	×	4000	×	6000	56.3	
	8.0	×	4000	×	4000	89.5	
14.3							
	508.0	×	4.0	×	4000	50.2	
6000					50.2		
5.0		×	4000	×	6000	62.6	

