

パイプサイズ・エキストラ表

SUS-304TPA (JIS G 3459)

外径 A	標準 B	標準	肉 厚															
			1.1~ 1.3	1.4~ 1.7	1.8~ 2.2	2.3~ 2.8	2.9~ 3.4	3.5~ 4.4	4.5~ 5.4	5.5~ 6.1	6.2~ 8.0	8.1~ 10.0	11.0~ 12.0	13.0~ 14.9	15.0~ 16.9	17.0~ 18.0		
			1.2	1.5	2.0	2.5	3.0	4.0	5.0	6.0	8.0	10.0	12.0	14.0	16.0	18.0	19.0	
6	1/8	10.5		550	500													
8	1/4	13.8	560	420	340		400											
10	3/8	17.3	380	320	240	250	250											
15	1/2	21.7	310	260	190	150	100											
20	3/4	27.2	260	200	150	110	60											
25	1	34.0	240	150	110	80	30	60										
32	1 1/4	42.7	230	140	100	70	20	50										
40	1 1/2	48.6	210	120	70	40	Base	20	100									
50	2	60.5		110	70	40		40	100									
65	2 1/2	76.3			70	40		40	50	140								
80	3	89.1			70	40		40	50	140								
90	3 1/2	101.6			80	50		30	50		160							
100	4	114.3			80	50		30	30	60	160							
125	5	139.8			150	80		10	20	30	60	200						
150	6	165.2						10	20	30	60		200					
200	8	216.3						30	20	20	30	60	120	200				
250	10	267.4						80	70	70	70	100	100			250		
300	12	318.5					90	80	80	80	100	100				250		

SUS-304TPY (JIS G 3468)

外径 A	標準 B	標準	肉 厚														
			1.1~ 1.3	1.4~ 1.7	1.8~ 2.2	2.3~ 2.8	2.9~ 3.4	3.5~ 4.4	4.5~ 5.4	5.5~ 6.1	6.2~ 8.0	8.1~ 10.0	11.0~ 12.0	13.0~ 14.9	15.0~ 16.9	17.0~ 18.0	
			1.2	1.5	2.0	2.5	3.0	4.0	5.0	6.0	8.0	10.0	12.0	14.0	16.0	18.0	19.0
350	14	355.6						40	Base	20	80	100					150
400	16	406.4					40	20		80	100						
450	18	457.2						40	20	20	40	80	120	120			
500	20	508.0						80	80	60	80	80	120	120	120		
550	22	558.8							100	80	100	120	150	150	150		
600	24	609.6								80	100	120	150	150	150	150	
650	26	660.4								100	100	120	150	150	150	150	
700	28	711.2								120	120	140	170	170	170	170	
750	30	762.0								120	120	140	170	170	170	170	
800	32	812.8								140	120	140	170	170	170	170	
850	34	863.6								140	120	140	170	170	170	170	
900	36	914.4								140	120	140	170	170	170	170	
950	38	965.2									140	140	170	170	170	170	
1000	40	1016.0									140	140	170	170	170	170	