

純チタン丸棒 (JIS H 4650)

T B 3 4 0 H

| 仕上 | 径 (mm) | 長さ (mm) | 質量 (kg/M) | |
|-----|-----------|------------|--------------|-------|
| P M | 10 | × | 4000 | 0.354 |
| " | 12 | × | 4000 | 0.51 |
| " | 13 | × | 4000 | 0.598 |
| " | 14 | × | 4000 | 0.694 |
| " | 15 | × | 4000 | 0.797 |
| " | 16 | × | 4000 | 0.907 |
| " | 18 | × | 4000 | 1.15 |
| " | 20 | × | 4000 | 1.42 |
| " | 22 | × | 4000 | 1.71 |
| " | 25 | × | 4000 | 2.21 |
| " | 28 | × | 4000 | 2.78 |
| " | 30 | × | 4000 | 3.19 |
| " | 32 | × | 4000 | 3.63 |
| " | 35 | × | 4000 | 4.34 |
| " | 38 | × | 4000 | 5.11 |
| " | 40 | × | 4000 | 5.67 |
| " | 42 | × | 4000 | 6.25 |
| " | 45 | × | 4000 | 7.17 |
| " | 50 | × | 4000 | 8.86 |
| " | 55 | × | 4000 | 10.7 |
| " | 60 | × | 4000 | 12.7 |
| " | 65 | × | 4000 | 15.0 |
| " | 70 | × | 4000 | 17.4 |
| " | 75 | × | 4000 | 19.9 |
| " | 80 | × | 4000 | 22.7 |
| " | 85 | × | 4000 | 25.6 |
| " | 90 | × | 4000 | 28.7 |
| " | 95 | × | 4000 | 32.0 |

T B 3 4 0 H

| 仕上 | 径 (mm) | 長さ (mm) | 質量 (kg/M) | |
|-----|-----------|------------|--------------|-------|
| T M | 100 | × | 4000 | 35.4 |
| " | 110 | × | 3000 | 42.9 |
| " | 120 | × | 3000 | 51.0 |
| " | 130 | × | 3000 | 59.8 |
| " | 140 | × | 3000 | 69.4 |
| " | 150 | × | 3000 | 79.7 |
| " | 160 | × | 3000 | 90.7 |
| " | 170 | × | 1500 | 102.0 |
| " | 180 | × | 1500 | 115.0 |
| " | 190 | × | 1500 | 128.0 |
| " | 200 | × | 1500 | 142.0 |
| " | 210 | × | 1500 | 156.0 |
| " | 220 | × | 1500 | 171.0 |
| " | 230 | × | 1500 | 187.0 |
| " | 240 | × | 1500 | 204.0 |
| " | 250 | × | 1500 | 221.0 |
| " | 260 | × | 1500 | 239.0 |

P M : 圧延ピーリング品 T M : 鍛造ピーリング品